

Endoscope for medical use, comprises transmitter which transmits observed image through wireless signal to external receiver

Patent Number: ☐ DE10028081

Publication date: 2001-02-22

Inventor(s): OUCHI TERUO (JP)

Applicant(s): ASAHI OPTICAL CO LTD (JP)

Requested Patent: ☐ JP2000342526

Application Number: DE20001028081 20000607

Priority Number(s): JP19990160031 19990607

IPC Classification: A61B1/005; A61B1/04; A61B1/273; A61B1/31; A61B5/07; G02B23/24

EC Classification: G02B23/24D, A61B1/005B, A61B1/05, A61B5/07B

Equivalents:

Abstract

The endoscope comprises a flexible tube (13) which assumes profile of the cavity of the organ. An illumination window (16) equipped with light emitting diode (16a) and an observation device (15) are provided within the tube. The tube is provided with power source. The observed image is transmitted by the transmitter as wireless signal to the external receiver.

Data supplied from the esp@cenet database - I2

4

Endoscope for medical use, comprises transmitter which transmits observed image through wireless signal to external receiver

Patent Number: ☐ DE10028081

Publication date: 2001-02-22

Inventor(s): OUCHI TERUO (JP)

Applicant(s): ASAHI OPTICAL CO LTD (JP)

Requested Patent: ☐ JP2000342526

Application Number: DE20001028081 20000607

Priority Number(s): JP19990160031 19990607

IPC Classification: A61B1/005; A61B1/04; A61B1/273; A61B1/31; A61B5/07; G02B23/24

EC Classification: G02B23/24D, A61B1/005B, A61B1/05, A61B5/07B

Equivalents:

Abstract

The endoscope comprises a flexible tube (13) which assumes profile of the cavity of the organ. An illumination window (16) equipped with light emitting diode (16a) and an observation device (15) are provided within the tube. The tube is provided with power source. The observed image is transmitted by the transmitter as wireless signal to the external receiver.

Data supplied from the esp@cenet database - I2